

Acquisition and Reproduction of Color Images:

Colorimetric and Multispectral Approaches

by

Jon Y. Hardeberg, Ph.D.

Dissertation.com • USA • 2001

*Acquisition and Reproduction of Color Images:
Colorimetric and Multispectral Approaches*

Copyright © 1999–2001 Jon Hardeberg
All rights reserved.

Dissertation.com
USA • 2001

ISBN: 1-58112-135-0

additional information and color ebook edition at:
www.dissertation.com/library/1121350a.htm

Preface

In the last two decades we have seen the field of digital color imaging emerging from specialized scientific applications, into being a part of the daily lives of most people in industrialized countries. Broadcast television, computers, newspapers and magazines, are just a few examples of technologies relying on digital color imaging.

The increased use of color has brought with it new challenges and problems. Digital color imaging is a research field with great prospects, since many problems are still unsolved.

One typical case that illustrates the problems that needs to be solved is that of an e-commerce business. Prospective customers use the World Wide Web to evaluate their products, typically by visualizing them on the computer monitor or by printing the product images on a desktop printer. If the customer decides to buy, and the color of the delivered product is not what she expected, she might decide to return it.

The book you're holding in your hands (or maybe you're reading it on your computer or eBook device) is the second edition of my Ph.D. dissertation. It is my hope that this book may be of service to the academic and industrial color imaging community, in many ways:

- As support for learning and teaching.
- Through the advances in the state-of-the-art represented by the proposed methods for the acquisition and reproduction of high quality digital color images.
- By advocating the multispectral approach to color imaging, that is to

use more than three color channels, in order to overcome the problems of metamerism.

- By giving ideas for further research concerning the technology, science, and art of color imaging.

Finally, I have to apologize that there's no color in the printed edition of this book. I find it amazing that color printing of a book like this is still not found to be cost-effective, even using an on-demand printing model. The only consolation in this is that I don't expect to be out of work for many many years to come!

Redmond, Washington, USA, June 2001

Abstract

The goal of the work reported in this dissertation is to develop methods for the acquisition and reproduction of high quality digital color images. To reach this goal it is necessary to understand and control the way in which the different devices involved in the entire color imaging chain treat colors. Therefore we addressed the problem of *colorimetric characterization* of scanners and printers, providing efficient and colorimetrically accurate means of conversion between a device-independent color space such as the CIELAB space, and the device-dependent color spaces of a scanner and a printer.

First, we propose a new method for the colorimetric characterization of color scanners. It consists of applying a non-linear correction to the scanner RGB values followed by a 3rd order 3D polynomial regression function directly to CIELAB space. This method gives very good results in terms of residual color differences. The method has been successfully applied to several color image acquisition devices, including digital cameras. Together with other proposed algorithms for image quality enhancements it has allowed us to obtain very high quality digital color images of fine art paintings.

An original method for the colorimetric characterization of a printer is then proposed. The method is based on a computational geometry approach. It uses a 3D triangulation technique to build a tetrahedral partition of the printer color gamut volume and it generates a surrounding structure enclosing the definition domain. The characterization provides the inverse

transformation from the device-independent color space CIELAB to the device-dependent color space CMY, taking into account both colorimetric properties of the printer, and color gamut mapping.

To further improve the color precision and color fidelity we have performed another study concerning the acquisition of multispectral images using a monochrome digital camera together with a set of $K > 3$ carefully selected color filters. Several important issues are addressed in this study. A first step is to perform a spectral characterization of the image acquisition system to establish the spectral model. The choice of color chart for this characterization is found to be very important, and a new method for the design of an optimized color chart is proposed. Several methods for an optimized selection of color filters are then proposed, based on the spectral properties of the camera, the illuminant, and a set of color patches representative for the given application. To convert the camera output signals to device-independent data, several approaches are proposed and tested. One consists of applying regression methods to convert to a color space such as CIEXYZ or CIELAB. Another method is based on the spectral model of the acquisition system. By inverting the model, we can estimate the spectral reflectance of each pixel of the imaged surface. Finally we present an application where the acquired multispectral images are used to predict changes in color due to changes in the viewing illuminant. This method of illuminant simulation is found to be very accurate, and it works well on a wide range of illuminants having very different spectral properties. The proposed methods are evaluated by their theoretical properties, by simulations, and by experiments with a multispectral image acquisition system assembled using a CCD camera and a tunable filter in which the spectral transmittance can be controlled electronically.

Key words

Color imaging, colorimetry, colorimetric characterization, multispectral imaging, spectral characterization, filter selection, spectral reconstruction.

Acknowledgements

The work described in this document has been carried out at the Signal and Image Processing Department at the Ecole Nationale Supérieure des

Télécommunications (ENST) in Paris, France. This endeavor would not have been completed without the support and help of many people. You all deserve thanks! Running the risk of forgetting someone important, I will mention some of you in particular.

First of all, I would like to thank my advisors Francis Schmitt and Hans Brettel. Thanks for showing me the way into the wonderful world of color, and for guiding and encouraging me throughout my tenure at the ENST. A big thank you goes then to all my colleagues and friends at the ENST. To the former and present Ph.D. students with whom I have shared moments of work and pleasure: Anne, Bert, Dimitri, Florence, Geneviève, Jean-Pierre, Jorge, Lars, Maria-Elena, Mehdi, Raouf, Selim, Sophie, Sudha, Wirawan, Yann, and many others. You have meant a great deal to me, and I sincerely hope to be able to stay in touch with you! To those of you who have worked with me on colorful projects: Bahman, Brice, Frédéric, Henri, Ingeborg, Jean-Pierre. To our relations in the industry, for showing me that my research could be able to solve some real problems out there.

I thank the members of the jury, Jean-Marc Chassery, Jean-François Le Nest, Khadi Bouatouch, and Roger D. Hersch, for your fruitful questions, comments and suggestions, and for honoring me by your presence at my defence. Furthermore, I would like to thank the organizing committees of the international conferences I have attended, for accepting the papers I submitted. Not only has this allowed me to present my work, and learn about the work of other researchers in the field of color imaging, it has given me the opportunity to meet and discuss with several inspiring individuals. I have seen that the world of color is a small one, after all.

Funding has been provided by the Norwegian Research Council (Norges Forskningsråd). Its financial support is of course gratefully acknowledged.

I am also very grateful to Dan and RanDair at Conexant Systems, Inc. for giving me a great opportunity to continue to work in this enchanting field.

Finally, I cannot imagine doing anything without you, Kristine. Thank you for giving me a reason to move to Paris, thank you for putting up with me through times of hard pressure, thank you for my two lovely children, Pauline and Samuel, and most of all, thank you for being you.

Kirkland, Washington, USA, November 1999

About the author

Jon Y. Hardeberg received his sivilingeniør (M.Sc.) degree in signal processing from the Norwegian Institute of Technology (Trondheim, Norway) in 1995. He received his Ph.D. from the Ecole Nationale Supérieure des Télécommunications (Paris, France) in February 1999. His Ph.D. research concerned color image acquisition and reproduction, with applications in facsimile, fine-art paintings, and multi-spectral imaging. He is currently employed with Conexant Systems, Inc., where he designs, implements, and evaluates color imaging system solutions for multifunction peripherals and other imaging devices and systems. His professional memberships include IS&T, SPIE, and ISCC.

About this book

Hardeberg, Jon Yngve, **Acquisition and Reproduction of Color Images: Colorimetric and Multispectral Approaches**. A dissertation submitted in partial fulfillment of the degree of "Docteur de l'Ecole Nationale Supérieure des Télécommunications", Paris, France, February 1999.

First edition published in 1999 by Ecole Nationale Supérieure des Télécommunications, 46, rue Barrault, F-75634 Paris Cedex 13, France, under the title "Acquisition et reproduction d'images couleur : approches colorimétrique et multispectrale," Publication ENST 99 E 021.

Second edition published in 2001 by Universal Publishers / dissertation.com, 7525 NW 61 Terrace, Suite 2603, Parkland, FL 33067-2421.

Changes from the first edition include layout, adding of a List of Tables and a List of Figures, correction of miscellaneous typographical errors, translation to American English (you know, *color* instead of *colour*, etc.), modifications to Figures 2.7 on page 21 and 3.11 on page 68, modifications to the numbering of Figures and Equations, and this preface.

Further information

More information about the described research can be found at the following locations:

- At <http://color.hardeberg.com/>
- By contacting the author by E-mail: jon.hardeberg@conexant.com, jon@hardeberg.com
- By contacting Prof. Francis Schmitt or Dr. Hans Brettel by E-mail: schmitt@tsi.enst.fr, brettel@tsi.enst.fr, or through the following address: Ecole Nationale Supérieure des Télécommunications, Département TSI, 46, rue Barrault, F-75634 Paris Cedex 13, France

Contents

Preface	i
Contents	xi
List of Figures	xvii
List of Tables	xx
1 Introduction	1
1.1 Motivation	1
1.2 Dissertation outline	3
1.3 Notation used throughout this document	5
2 Color and imaging	7
2.1 Introduction	7
2.2 Light and surfaces	9
2.3 Color vision	10
2.4 Colorimetry	14
2.4.1 Grassmann's laws	15
2.4.2 Tristimulus space	16
2.4.3 Color matching	17
2.4.4 Color matching functions	20
2.4.5 Metamerism	20
2.4.6 CIE standard illuminants	21

2.4.7	CIE standard observers	22
2.4.8	Uniform color spaces and color differences	26
2.5	Color imaging	32
2.5.1	Color management	32
2.5.2	Digital image acquisition	37
2.5.3	Digital image reproduction	39
2.5.4	Multi-channel imaging	44
2.6	Conclusion	46
3	Colorimetric scanner characterization	47
3.1	Introduction	48
3.2	Characterization methodology	49
3.2.1	Regression	50
3.2.2	Linearization of the scanner RGB values	53
3.2.3	Choice of the approximation function	59
3.3	Experimental results	61
3.3.1	Evaluation measures	61
3.3.2	Results	62
3.3.3	Generalization	64
3.3.4	Comparison of results with and without character- ization	64
3.4	Conclusion	68
4	High quality image capture	71
4.1	Introduction	72
4.2	High resolution digital cameras, a review	74
4.2.1	The VASARI project	74
4.2.2	Further developments under the MARC project	75
4.3	Experimental setup and initial calibration	76
4.3.1	General setup	77
4.3.2	CCD calibration	77
4.4	Correction algorithms	80
4.4.1	Light distribution correction	80
4.4.2	Inter-channel registration	81
4.4.3	Colorimetric correction	82
4.5	Post-processing	83
4.5.1	Mosaicing	84
4.5.2	Visualization and reproduction	84
4.5.3	Colorimetric analysis of fine art paintings	85

4.6	Conclusion	85
5	Colorimetric printer characterization	89
5.1	Introduction	89
5.2	Methodology overview	92
5.3	Inner structure	94
5.3.1	Delaunay triangulation of the CMY color gamut	96
5.3.2	Transport of the triangulation into CIELAB space	97
5.4	Surrounding structure	99
5.4.1	Construction of the surrounding structure in CIE- LAB space	101
5.4.2	Determination of the visibility directions	102
5.4.3	Determination of the fictive points in CIELAB space	107
5.4.4	Triangulation of the surrounding structure	111
5.5	CIELAB-to-CMY transformation	114
5.5.1	Localization of a CIELAB point in the 3D structure	114
5.5.2	Irregular tetrahedral interpolation	115
5.5.3	Color gamut mapping	117
5.6	Conclusion	118
6	Multispectral image acquisition: Theory and simulations	121
6.1	Introduction	122
6.2	Spectral characterization of the image acquisition system	123
6.2.1	Image acquisition system model	124
6.2.2	Spectral sensitivity function estimation	126
6.2.3	Discussion on spectral characterization	140
6.3	Spectral reflectance estimation from camera responses	142
6.3.1	Pseudo-inverse solution	143
6.3.2	Reconstruction exploiting <i>a priori</i> knowledge of the imaged objects	144
6.3.3	Evaluation of the spectral reflectance reconstruction	145
6.4	Analysis of spectral reflectance data sets	145
6.4.1	Principal Component Analysis	147
6.4.2	Effective dimension	148
6.4.3	Application to real reflectance data sets	151
6.4.4	Discussion	153
6.5	Choice of the analysis filters	157
6.5.1	Filter selection methods	157
6.5.2	Discussion	162

6.6	Evaluation of the acquisition system	164
6.7	Multimedia application: Illuminant simulation	167
6.7.1	Illuminant simulation using CIELAB space	167
6.7.2	Illuminant simulation using multispectral images	169
6.7.3	Evaluation of the two illuminant simulation methods	169
6.8	Conclusion	172
7	Multispectral image acquisition: Experimentation	175
7.1	Introduction	176
7.2	Equipment	176
7.2.1	CCD camera	176
7.2.2	Tunable filter	177
7.2.3	Illumination	179
7.2.4	Color chart	180
7.3	Illumination and dark current compensation	182
7.4	Spectral sensitivity estimation	182
7.4.1	Preliminary experiment	183
7.4.2	Estimation results	185
7.5	Experimental multispectral image acquisition	186
7.5.1	Model evaluation	190
7.6	Recovering colorimetric and spectrophotometric image data	192
7.6.1	Model-based spectral reconstruction	192
7.6.2	Direct colorimetric regression	198
7.7	Conclusion	202
8	Conclusions and perspectives	205
	Bibliography	211
	Citation index	235
	Appendices	
A	Mathematical background	243
A.1	Least mean square (LMS) error minimization	243
A.1.1	1D Interpolation Functions of degree n	243
A.1.2	3D interpolation function of the first degree	245
A.1.3	3D interpolation function of general degree n	247
A.2	Principal Component Analysis (PCA)	248
A.3	Singular Value Decomposition (SVD)	252

A.3.1	SVD of Jolliffe (1986)	252
A.3.2	SVD of Pratt (1978)	253
A.3.3	Application of the SVD to PCA	254
A.3.4	Application of the SVD to LMS minimization — pseudoinverse	256
B	Color transformation by 3D interpolation	257
C	Scanner characterization data	263
D	Some printer gamuts	277
E	Gamut mapping techniques	289
F	Bibliography on the dimensionality of spectral reflectances	293

List of Figures

2.1	<i>Newton's experiment with sunlight and a prism.</i>	9
2.2	<i>A simple spectral model for the interaction between light and surfaces.</i>	11
2.3	<i>Normalized spectral sensitivity curves of the three different types of cones.</i>	12
2.4	<i>Human vision of a reflective object.</i>	13
2.5	<i>(R,G,B)-tristimulus space.</i>	18
2.6	<i>Principle of trichromatic color matching.</i>	19
2.7	<i>Two metameric spectra.</i>	21
2.8	<i>Relative spectral power distributions of standard illuminants.</i>	23
2.9	<i>CIE XYZ color matching functions.</i>	25
2.10	<i>Chromaticity diagram.</i>	27
2.11	<i>Munsell loci of constant hue and chroma.</i>	30
2.12	<i>Different digital imaging devices connected to a central computer.</i>	33
2.13	<i>Different digital imaging devices connected in a color management system.</i>	34
2.14	<i>A typical Color Management System architecture.</i>	35
2.15	<i>An example of a color management system for color facsimile.</i>	36
2.16	<i>An ideal subtractive color reproduction system.</i>	41
2.17	<i>Comparison of ideal and real printer inks.</i>	43
3.1	<i>The scanner characterization process.</i>	50

3.2	<i>The transformation from scanner RGB-space to CIELAB-space using the function $g^l(\mathbf{P})$.</i>	51
3.3	<i>1D example of first and third order polynomial regression functions.</i>	52
3.4	<i>Linearization of the scanner output values.</i>	54
3.5	<i>Linearization curve with a global approach.</i>	56
3.6	<i>Illustration of a piecewise linear linearization curve.</i>	57
3.7	<i>The linearization curves obtained with a piecewise linear approach.</i>	58
3.8	<i>Error histograms for the FUJI IT8.7/2 chart.</i>	65
3.9	<i>Error distribution for the FUJI IT8.7/2 chart.</i>	66
3.10	<i>Visualization of the characterization error using the linear regression method.</i>	67
3.11	<i>Visualization of the characterization error using the proposed characterization method.</i>	68
4.1	<i>Traditional image acquisition process.</i>	72
4.2	<i>Entirely digital image acquisition process.</i>	72
4.3	<i>General setup and CCD calibration.</i>	78
4.4	<i>Characterization and correction of the CCD electronic gain.</i>	79
4.5	<i>Flowchart of the main data processing.</i>	80
4.6	<i>RGB misalignment by optical color dispersion.</i>	82
4.7	<i>Example of inter-channel registration.</i>	83
4.8	<i>Various post-processing algorithms applied to the acquired CIELAB images.</i>	84
4.9	<i>Colorimetric analysis of “Le Forum” by Jean-Baptiste Camille Corot.</i>	86
5.1	<i>Printer characterization.</i>	92
5.2	<i>Triangulated CMY color gamut cube and its corresponding geometrically deformed CIELAB color gamut.</i>	93
5.3	<i>Octahedron surrounding the printer color gamut and the definition domain in CIELAB space.</i>	95
5.4	<i>2D illustrations of the no-mirrored-tetrahedron property.</i>	98
5.5	<i>A 2D example of a structure with two faces.</i>	102
5.6	<i>Gauss sphere.</i>	103
5.7	<i>Principal normal direction \mathbf{N}_p associated with a Gauss sphere portion G_p.</i>	103

5.8	<i>Intersection of the Gauss sphere and the plane defined by the outward normal.</i>	104
5.9	<i>A cone centered on \mathbf{N}_p.</i>	106
5.10	<i>Determination of the visibility direction \mathbf{D}_f.</i>	107
5.11	<i>Determination of the nearest kernel point.</i>	108
5.12	<i>Determination of the final surrounding structure.</i>	110
5.13	<i>Triangulation of the surrounding structure.</i>	112
5.14	<i>Construction of a surrounding octahedron in CMY space.</i>	113
5.15	<i>Surrounding structure in CMY space.</i>	113
5.16	<i>Tetrahedron division for interpolation.</i>	116
5.17	<i>Gamut compression.</i>	118
6.1	<i>Schematic view of the image acquisition process.</i>	125
6.2	<i>Spectral sensitivities of the acquisition system.</i>	128
6.3	<i>Simulation of the acquisition system and evaluation of the spectral characterization methods.</i>	128
6.4	<i>RMS sensitivity estimation error for different numbers of bits using the pseudoinverse (PI) method.</i>	131
6.5	<i>Sensitivity estimation for different numbers of bits using the pseudoinverse (PI) method.</i>	131
6.6	<i>RMS sensitivity estimation error for different levels of quantization noise.</i>	133
6.7	<i>Optimal number of PE's for different levels of acquisition noise and resulting RMS estimation errors.</i>	134
6.8	<i>Camera sensitivity estimation using the PE method with 10 and 20 PE's, and quantizing on 10 and 8 bits.</i>	135
6.9	<i>Munsell notations and CIELAB coordinates for the chosen Munsell patches.</i>	137
6.10	<i>Camera sensitivity estimation using the PE method with 10 and 20 principal eigenvectors, with different sets of 20 reflectances.</i>	138
6.11	<i>PCA analysis of different sets of 20 reflectances.</i>	139
6.12	<i>Reconstruction of the spectral reflectance of two pigments from the camera responses using seven filters.</i>	146
6.13	<i>An example of the singular values of the reflectance spectra of the pigments of the National Gallery chart.</i>	149
6.14	<i>The mean and maximal spectral reconstruction error compared to the energy contained in the first PCs.</i>	150
6.15	<i>Examples of reflectance spectra from the different databases.</i>	152

6.16	<i>Comparison of singular values of the 5 different databases in logarithmic scale.</i>	155
6.17	<i>Comparison of the accumulated energy of the different databases.</i>	156
6.18	<i>Illustration of the computational complexity involved when comparing all possible filter combinations.</i>	159
6.19	<i>The complete chain of multi-channel image acquisition system with the final spectral reconstruction step.</i>	164
6.20	<i>An acquisition system using seven filters.</i>	165
6.21	<i>Evaluation of an acquisition system using seven filters.</i>	166
6.22	<i>Relative spectral radiances of the five illuminants used in the experiment.</i>	171
6.23	<i>Histograms of simulation errors for the CIELAB method and the multispectral methods using 5, 7, and 10 filters.</i>	172
6.24	<i>Simulation results for a seven-channel acquisition system with the illuminants A, F2, D50 and a LPS lamp.</i>	173
7.1	<i>Typical spectral sensitivity of PCO SensiCam CCD camera as given by the manufacturer.</i>	177
7.2	<i>Spectral transmittances of the LTCF filter.</i>	179
7.3	<i>The Macbeth ColorChecker Color Rendition Chart used in our experiments.</i>	181
7.4	<i>Verification of linearity of the SensiCam CCD camera after normalization for black current and lighting distribution.</i>	183
7.5	<i>Comparison of real experimental camera response to the predicted response using linear acquisition models.</i>	184
7.6	<i>Illustration of error induced when using a wavelength range of 400 to 700 nm.</i>	185
7.7	<i>Spectral sensitivity estimation of the image acquisition system consisting of a PCO SVGA SensiCam CCD camera and a tungsten halogen illuminant.</i>	187
7.8	<i>Comparison of estimated and observed camera responses using the different estimations</i>	188
7.9	<i>Nine channels of a multispectral image of the Macbeth color checker.</i>	189
7.10	<i>RMS camera response estimation errors over the 24 Macbeth patches using the 17 different filters.</i>	191
7.11	<i>Observed and predicted camera responses for the 24 Macbeth patches using the 17 different filters.</i>	193

7.12	<i>Observed and predicted camera responses using separate α_k for each channel.</i>	194
7.13	<i>Spectral reconstruction with the original model.</i>	196
7.14	<i>Spectral reconstruction with the modified model.</i>	197
7.15	<i>Spectral reconstruction of three patches from the camera responses, with the parameter r varying from 1 to 9.</i>	198
7.16	<i>Examples of colorimetric reconstructions using three and seven channel images and linear regression.</i>	200
A.1	<i>Illustration of PCA.</i>	250
A.2	<i>SVD according to Jolliffe.</i>	252
A.3	<i>SVD according to Pratt.</i>	253
A.4	<i>The matrix \mathbf{W} containing the singular values of \mathbf{X}.</i>	253
B.1	<i>Partition of the RGB-space into cubic sub-spaces.</i>	259
B.2	<i>The two possible schemes for dividing a cube into five tetrahedrons.</i>	260
B.3	<i>The division of a tetrahedron into four sub-tetrahedra.</i>	261
B.4	<i>3D tetrahedron interpolation color transformation algorithm.</i>	262
C.1	<i>The AGFA IT8.7/2 target scanned using an AGFA Arcus 2 flatbed scanner.</i>	266
D.1	<i>The regular color chart used for the printer characterization and for defining the color gamuts.</i>	278
D.2	<i>Two views of the color gamut of the Mitsubishi S340-10 sublimation printer.</i>	279
D.3	<i>Two views of the color gamut of the Epson Stylus 2 ink jet printer using coated paper.</i>	280
D.4	<i>Two views of the color gamut of the Epson Stylus 2 ink jet printer used on glossy paper.</i>	281
D.5	<i>Two views of the color gamut of the Epson Stylus 2 ink jet printer using normal paper.</i>	282
D.6	<i>Two views of the color gamut of the Kodak sublimation printer.</i>	283
E.1	<i>Gamut clipping methods.</i>	291
E.2	<i>Gamut compression.</i>	292

List of Tables

2.1	<i>Rule of thumb for the practical interpretation of ΔE_{ab}^* measuring the color difference between two color patches viewed side by side.</i>	31
3.1	<i>Results of the characterization methods for the AGFA Arcus II scanner, with the AGFA IT8.7/2 color chart.</i>	63
3.2	<i>Results of the different characterization methods for the AGFA Arcus II scanner, with the FUJI IT8.7/2 color chart.</i>	63
3.3	<i>Results for the ($p=1/3$, T3, LAB) method and the AGFA IT8.7/2 color chart using different numbers of patches for training and testing.</i>	66
6.1	<i>Signal-to-noise ratio (SNR) for different number of bits used for quantization.</i>	130
6.2	<i>Comparison of the results of a PCA analysis of the optimal/heuristic selections of Munsell patches and of the Macbeth ColorChecker.</i>	139
6.3	<i>Root-mean-square spectral sensitivity estimation errors using the different methods.</i>	141
6.4	<i>Estimation errors for the optimal/heuristic data sets relative to the results obtained when using the complete set of 1269 Munsell chips.</i>	141
6.5	<i>Accumulated energy of the different databases.</i>	154
6.6	<i>Effective dimensions D_e for the different databases.</i>	155

6.7	<i>Comparison of key properties of the proposed filter selection methods.</i>	163
6.8	<i>Comparison of the RMS spectral reconstruction error for varying number of filters using the reconstruction operator \mathbf{Q}_1 (cf. Section 6.3).</i>	166
6.9	<i>Mean and maximal ΔE_{94}^* errors obtained for the simulations of five illuminants with four different methods: CIE-LAB space used as a color appearance model and the three multispectral approaches using 5, 7 and 10 filters, respectively.</i>	170
7.1	<i>Integration times t_k and normalization factors k_{I_k} for the 17 channels of our experimental multispectral image acquisition of the Macbeth chart.</i>	190
7.2	<i>Mean and maximal errors for different filter sets and different spectral reconstruction methods.</i>	199
7.3	<i>Resulting colorimetric reconstruction errors (using CIE illuminant A) using regression methods and different numbers of filters.</i>	201
7.4	<i>Resulting reconstruction errors (illuminant A) using combinatorial search to select the best set of filters among the 17 compared to the heuristic selections of Table 7.3.</i>	201
C.1	<i>Regression polynomial coefficients for the scanner characterization.</i>	265
C.2	<i>Scanner characterization data.</i>	267
D.1	<i>Printer RGB values and CIELAB values measured using a SpectraScan spectrophotometer for the $5 \times 5 \times 5$ regular color chart printed on a Mitsubishi S340-10 sublimation printer</i>	284

Chapter 1

Introduction

1.1 Motivation

The use of color in imaging continues to grow at an ever-increasing pace. Every day, most people in the industrialized parts of the world are users of color images that come from a wide range of imaging devices; for example color photographs, magazines, and television at home, computers with color displays, and color printers in the office.

As long as the colors are found to be approximately as expected, people are generally happy with their images. However, with the increased use of color images, people's quality requirements also have increased considerably. Just a few years ago, a computer graphics system capable of producing 256 different colors was more than enough for most users, while today, most computers that are sold have *true color* capabilities, being able to produce 16.7 million¹ colors.

Furthermore, several professions have particular needs for high-quality color images. Artists are very concerned about colors in their works, and so are the art historians and curators studying their works. The printing, graphic arts, and photography industries have been concerned about color imaging for a long time. Most of the color imaging standards and equip-

¹Note that this number represents only the number of different colors that can be specified to the monitor ($2^8 \cdot 2^8 \cdot 2^8 = 16777216$); the actual number of distinguishable resulting colors is much lower, approximately on the order of 1 million (Pointer and Attridge, 1998).

ment used today have their roots in these industries. But the past twenty years have seen the field of digital color imaging emerging from specialized scientific applications into the mainstream of computing. Color is also extremely important in several other fields, such as the textile and clothing industry, automotive industry, decoration and architecture.

Digital color imaging systems process electronic information from various sources: images may come from the Internet, a remote sensing device, a local scanner, etc. After processing, a document is usually compressed and transmitted to several places via a computer network for viewing, editing or printing. To achieve color consistency throughout such a widely distributed system, it is necessary to understand and control the way in which the different devices involved in the entire color imaging chain treat colors. Each scanner, monitor, printer, or other color imaging device, senses or displays color in a different, device-dependent, way. One approach to exchanging images between these devices is to calibrate each color image acquisition and reproduction device to a device-independent color space. The exchange of images can then be done in this color space, which should conform to international standards.

However, colors represent an important but nevertheless limited aspect of the objects that surround us. They correspond to the human perception of its surface under given light conditions. For the needs of, for example, an art curator wanting to control any changes or ageing of the materials in a fine arts painting, or a publisher wanting extra high-fidelity color reproduction, it becomes necessary to provide a more complete spectral analysis of the objects. This requires technology and devices capable of acquiring multispectral images. A multispectral image may also be used to reproduce an image of the object, as it would have appeared under a given illuminant.

In this research, we have investigated several of the aspects mentioned above. We have developed novel algorithms for the colorimetric characterization of scanners and printers providing efficient and colorimetrically accurate means of conversion between a device-independent color space such as CIELAB, and the device-dependent color spaces of a scanner and a printer. Furthermore, we have developed algorithms for multispectral image capture using a CCD camera with carefully selected optical filters. The developed algorithms have been used for several applications, such as fine-arts archiving and color facsimile.

1.2 Dissertation outline

This thesis is organized as follows. Chapter 2 provides an introduction to light, objects, human color vision, and the interaction between them, gives an introduction to important elements of colorimetry, and finally presents the subject of color imaging.

In Chapter 3, a methodology for the colorimetric characterization of color scanners is proposed. It consists of applying a non-linear correction to the scanner RGB values followed by a 3rd order 3D polynomial regression function directly to CIELAB space. This method gives very good results in terms of residual color differences. This is partly due to the fact that the RMS error that is minimized in the regression corresponds to ΔE_{ab} , which is well correlated to visual color differences. The method has been successfully applied to several color image acquisition devices.

In Chapter 4, various techniques for the digital acquisition and processing of high quality and high definition color images using a CCD camera are developed. The techniques have been applied to fine arts paintings on several occasions, *e.g.* for the making of a CDROM on the French painter Jean-Baptiste Camille Corot (1796-1876).

A novel method for the colorimetric characterization of a printer is proposed in Chapter 5. The method is based on a computational geometry approach. It uses a 3D triangulation technique to build a tetrahedral partition of the printer color gamut volume and it generates a surrounding structure enclosing the definition domain. The characterization provides the inverse transformation from the device-independent color space CIELAB to the device-dependent color space CMY, taking into account both colorimetric properties of the printer, and color gamut mapping.

We construct two 3D structures which provide us with a partition of the space into two sets of non-intersecting tetrahedra, an inner structure covering the printer gamut (*i.e.* the full set of the printable colors), and a surrounding structure, the union of these two structures covering the entire definition domain of the CIELAB space. These 3D structures allow us to easily determine if a CIELAB point is inside or outside the printer color gamut, to apply a gamut mapping technique when necessary, and then to compute by irregular tetrahedral interpolation the corresponding CMY values. We establish thus an empirical inverse printer model. This algorithm has been protected by a patent, and is now transferred to industry and used in commercial color management software.

In Chapter 6, we describe a system for the acquisition of multispectral